



BUSCK







P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)	
0.06	0.9	203.5	1.1	1500	SB030/063	6270	
	0.78	225	0.9	1800		6270	
	0.58	276	0.8	2400		6270	
	0.47	319	0.7	3000		6270	
	0.35	306	0.6	4000		6270	
	0.28	360	0.4	5000		6270	
	0.6	330.4	1.1	2400	SB040/075	7380	
	0.47	377	0.8	3000		7380	
	0.35	355	0.7	4000		7380	
	0.28	419	0.5	5000		7380	
	0.5	405.9	1.4	3000	SB040/090	8180	
	0.35	365	1.3	4000		8180	
	0.28	431	1	5000		8180	
	0.09	280	2.7	4.1	5	SB025	439
		186.7	3.9	2.8	7.5		503
140		5.1	2.4	10	553		
93.3		7.3	1.6	15	633		
70		9.2	1.3	20	697		
46.7		12	1.1	30	798		
35		15	0.9	40	878		
280		2.7	6.7	5	SB030	597	
186.7		3.9	4.6	7.5		683	
140		5	3.6	10		752	
93.3		7.1	2.5	15		861	
70		9	2	20		948	
56		10	2	25		1021	
46.7		12	1.7	30		1085	
35		14	1.2	40		1194	
28		17	1	50		1286	
23.3		19	0.9	60		1367	
14		37.7	0.8	100		1620	
9.3		49	0.6	150		1830	
7		62	0.5	200		1830	
5.6		66	0.5	250		1830	
4.7		75	0.4	300		1830	
3.5		107	0.3	400	1830		
2.8		115	0.3	500	1830		
2.3		135	0.2	600	1830		
1.9		151	0.2	750	1830		
1.6		178	0.2	900	1830		
1.2		212	0.1	1200	1830		
0.9		247	0.1	1500	1830		
0.78		304	0.1	1800	1830		
0.58		340	0.1	2400	1830		
0.47		405	0.1	3000	1830		
28		19	2	50	SB040	2475	
23.3		21	1.7	60		2630	
17.5		26	1.3	80		2895	
14		29	1	100		3118	
4.7		87.6	0.8	300	SB030/040	3490	
3.5		106.7	1.2	400	SB030/050	4840	
2.8		123	1	500		4840	
2.3		159	0.9	600		4840	
1.9		185	0.8	750		4840	
1.6		212	0.7	900		4840	
1.6		200	1	900		6270	
1.2		263	0.9	1200	SB030/063	6270	
0.93		305	0.7	1500	6270		




P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)
0.09	0.9	359.7	1.1	1500		7380
	0.78	404	1	1800	SB040/075	7380
	0.58	496	0.7	2400		7380
	0.5	608.9	0.9	3000		8180
	0.35	548	0.8	4000	SB040/090	8180
0.12	280	3.6	5.1	5		597
	186.7	5.2	3.4	7.5		683
	140	6.7	2.7	10		752
	93.3	9.5	1.9	15		861
	70	12	1.5	20	SB030	948
	56	14	1.5	25		1021
	46.7	16	1.3	30		1085
	35	19	0.9	40		1194
	28	23	0.8	50		1286
	46.7	17.2	2.6	30		2087
	35	21	1.9	40		2298
	28	25	1.5	50	SB040	2475
	2.3	28	1.3	60		2630
	17.5	34	1	80		2895
	14	38	0.8	100		3118
	19.1	41.5	1.2	73.3		2833
	15.9	45	1.2	88		3011
	11.9	56	0.9	117.3	PC063+SB040	3314
	9.5	64.6	0.7	146.7		3490
	7.9	73	0.6	176		3490
	23.3	29	2.3	60		3610
	17.5	35	1.9	80	SB050	3973
	14	40	1.4	100		4280
	9.5	66	1.3	146.7		4840
	7.9	74	1.1	176		4840
	6.0	85	0.8	234.6	PC063+SB050	4840
	4.8	96	0.7	293.3		4840
	4.7	118.8	1.2	300		4840
	3.5	142	0.9	400	SB030/050	4840
	2.8	164	0.7	500		4840
	6.0	89	1.5	234.6		6270
	4.8	101	1.2	293.3	PC063+SB063	6270
	2.8	171.2	1.3	500		6270
2.3	208	1.1	600	SB030/063	6270	
1.9	241	0.9	750		6270	
1.6	324.9	1.2	900		7370	
1.2	399	0.9	1200	SB040/075	7380	
0.8	546.6	0.9	1800		8180	
0.58	695	0.9	2400	SB040/090	8180	
0.5	883.8	1.2	3000		10320	
0.35	784	1	4000		10320	
0.28	928	0.8	5000	SB050/110	10320	
0.18	280	5.3	3.4	5		597
	186.7	7.8	2.3	7.5		683
	140	10	1.8	10		752
	93.3	14	1.3	15	SB030	861
	70	18	1	20		948
	56	21	1	25		1021
	46.7	24	0.8	30		1085
	70	19.2	2	20		1824
	56	23	1.7	25	SB040	1964
	46.7	26	1.7	30		2087
	35	32	1.3	40		2298




P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)	
0.18	28	38	1	50	SB040	2475	
	23.3	43	0.8	60		2630	
	19.1	62	0.8	73.3	PC063+SB040	2833	
	15.9	69	0.8	88		3011	
	11.9	84	0.6	117.3		3314	
	35	32.9	2.3	40		3153	
	28	39	1.9	50	SB050	3397	
	23.3	43	1.6	60		3610	
	17.5	52	1.2	80		3973	
	14	60	0.9	100		4280	
	19.1	62	1.4	73.3		PC063+SB050	3889
	15.9	70	1.5	88	4132		
	11.9	86	1.1	117.3	4548		
	9.5	99	0.9	146.7	4840		
	7.9	112	0.7	176	4840		
	6.0	129	0.6	234.6	4840		
	9.5	101	1.7	146.7	PC063+SB063	6270	
	7.9	116	1.4	176		6270	
	6.0	135	1	234.6		6270	
	4.8	152	0.8	293.3		6270	
	3.5	221.5	1	400	SB030/063	6270	
	2.8	257	0.8	500		6270	
	2.3	362	1.1	600	SB040/075	7380	
	1.9	435	0.9	750		7380	
1.6	487	0.8	900	7380			
1.2	629.2	1	1200	SB040/090	8180		
0.93	735	0.8	1500		8180		
0.8	860.6	1.5	1800	SB050/110	10320		
0.58	1113	1.1	2400		10320		
0.22	280	6.5	2.8	5	SB030	597	
	186.7	10	1.9	7.5		683	
	140	12	1.5	10		752	
	93.3	17	1	15		861	
	70	22	0.8	20		948	
	93.3	18.5	2.2	15	SB040	1657	
	70	23	1.7	20		1824	
	56	28	1.4	25		1964	
	46.7	32	1.4	30		2087	
	35	39	1.1	40		2298	
	28	47	0.8	50		2475	
	28	47.3	1.5	50		SB050	3397
	23.3	53	1.3	60			3610
	17.5	64	1	80	3973		
	19.1	76	1.2	73.3	PC063+SB050	3889	
	15.9	84	1.2	88		4132	
	11.9	104	0.9	117.3		4548	
	9.5	123	1.4	146.7		6270	
	7.9	141	1.1	176		6270	
	4.7	210.5	1.1	300		SB030/063	6270
	3.5	271	0.8	400	6270		
	0.25	280	7.6	4.5	5	SB040	1149
		186.7	11	3.6	7.5		1315
		140	14	2.8	10		1447
93.3		21	1.9	15	1657		
70		27	1.5	20	1824		
56		32	1.2	25	1964		
46.7		36	1.3	30	2087		
35		44	0.9	40	2298		




P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)	
0.25	70	26.9	2.7	20	SB050	2503	
	56	32	2.2	25		2696	
	46.7	37	2.3	30		2865	
	35	46	1.7	40		3153	
	28	54	1.4	50		3397	
	23.3	60	1.1	60		3610	
	17.5	72	0.9	80		3973	
	19.1	86	1	73.4	PC071+SB050	3889	
	15.9	96	1.1	88.1		4132	
	11.9	119	0.8	117.5		4548	
	28	56.3	2.4	50	SB063	4440	
	23.3	63	2	60		4719	
	17.5	78	1.6	80		5193	
	14	87	1.4	100		5595	
	19.1	89	1.8	73.4	PC071+SB063	5083	
	15.9	98	2	88.1		5401	
	11.9	123	1.5	117.5		5945	
	9.5	140	1.2	146.9		6270	
	7.9	161	1	176.3		6270	
	6.0	185.6	0.7	235		6270	
	4.8	211	0.6	293.8		6270	
	17.5	81.9	2.3	80	SB075	6130	
	14	94	1.9	100		6603	
	9.5	148	1.7	146.9	PC071+SB075	7380	
7.9	170	1.4	176.3	7380			
6.0	195	1.1	235	7380			
4.8	225	0.9	293.8	7380			
3.5	336.3	1.1	400	SB040/075	7380		
2.8	384	0.8	500		7380		
2.3	511.8	1.2	600	SB040/090	8180		
1.9	598	0.9	750		8180		
1.6	667	0.8	900		8180		
1.2	943	1.3	1200	SB050/110	10320		
0.93	1064	1.2	1500		10320		
0.78	1195	1.1	1800		10320		
0.6	1624	1	2400	SB063/130	13500		
0.47	1935	0.8	3000		13500		
0.35	2046	0.6	4000		13500		
0.28	2430	0.5	5000		13500		
280	11.2	3	5		SB040	1149	
186.7	16	2.4	7.5	1315			
140	21	1.9	10	1447			
93.3	31	1.3	15	1657			
70	39	1	20	1824			
56	47	0.8	25	1964			
46.7	53	0.8	30	2087			
140	21.7	3.3	10	SB050		1987	
93.3	31	2.4	15			2274	
70	40	1.8	20			2503	
56	48	1.5	25		2696		
46.7	55	1.5	30		2865		
35	68	1.1	40		3153		
28	80	0.9	50		3397		
23.3	89	0.8	60		3610		
35	70.7	2.1	40		SB063	4122	
28	83	1.6	50			4440	
0.37	280	11.2	3	5	SB040	1149	
	186.7	16	2.4	7.5		1315	
	140	21	1.9	10		1447	
	93.3	31	1.3	15		1657	
	70	39	1	20		1824	
	56	47	0.8	25		1964	
	46.7	53	0.8	30		2087	
	140	21.7	3.3	10		SB050	1987
	93.3	31	2.4	15			2274
	70	40	1.8	20			2503
	56	48	1.5	25	2696		
	46.7	55	1.5	30	2865		
35	68	1.1	40	3153			
28	80	0.9	50	3397			
23.3	89	0.8	60	3610			
35	70.7	2.1	40	SB063	4122		
28	83	1.6	50		4440		




P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)
0.37	23.3	94	1.4	60	SB063	4719
	17.5	115	1.1	80		5193
	14	129	0.9	100		5595
	19.1	131	1.2	73.4	PC071+SB063	5083
	15.9	145	1.4	88.1		5401
	11.9	182	1	117.5		5945
	9.5	208	0.8	146.9		6270
	23.3	98.4	2	60	SB075	5569
	17.5	121	1.6	80		6130
	14	139	1.3	100		6603
	19.1	135	1.8	73.4	PC071+SB075	6000
	15.9	151	1.9	88.1		6375
	11.9	188	1.5	117.5		7017
	9.5	218	1.1	146.9		7380
	7.9	251	0.9	176.3	7380	
	4.7	405.5	1	300	SB040/075	7380
	3.5	498	0.7	400		7380
	7.9	265	1.5	176.3	PC071+SB090	8180
	6.0	312	1.1	235		8180
	4.8	363	0.9	293.8		8180
	4.7	401.8	1.5	300	SB040/090	8180
	3.5	523	1.2	400		8180
	2.8	611	0.9	500		8180
	2.3	757	0.8	600		8180
1.9	949.5	1.3	750	SB050/110	10320	
1.6	1079	1.2	900		10320	
1.2	1396	0.8	1200		10320	
0.9	1674.1	1.1	1500	SB063/130	13500	
0.78	1887	0.9	1800		13500	
0.55	280	16.7	2	5	SB040	1149
	186.7	24	1.6	7.5		1315
	140	32	1.3	10		1447
	93.3	46	0.9	15		1657
	280	16.7	3.7	5	SB050	1577
	186.7	25	2.9	7.5		1805
	140	32	2.2	10		1987
	93.3	46	1.6	15		2274
	70	59	1.2	20		2503
	56	71	1	25		2696
	46.7	81	1	30		2865
	70	60.8	2.2	20	SB063	3272
	56	73	1.8	25		3524
	46.7	83	1.9	30		3745
	35	105	1.4	40		4122
	28	124	1.1	50		4440
	23.3	140	0.9	60		4719
	19.1	196	0.8	73.4	PC071+SB063	5083
	15.9	215	0.9	88.1		5401
	35	108.1	2	40	SB075	4865
	28	129	1.6	50		5241
	23.3	146	1.4	60		5569
	17.5	180	1.1	80		6130
	14	206	0.9	100		6603
	19.1	201	1.2	73.4		PC071+SB075
	15.9	229	1.3	88.1	6375	
	11.9	279	1	176.3	7017	
	18.7	205.4	1.2	75	PC080+SB075	6000
	15.6	230	1.3	90		6375




P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)	
0.55	11.7	284	1	120	PC080+SB075	7017	
	9.3	332	0.8	150		7380	
	17.5	189.1	1.5	80	SB090	6783	
	14	221	1.2	100		7306	
	15.6	239.7	2.3	90	PC080+SB090	7054	
	11.7	297	1.6	120		7764	
	9.3	355	1.3	150		8180	
	7.8	398	1	180		8180	
	5.8	477	0.8	240		8180	
	17.5	201.1	2.6	80		SB110	8571
	14	236	2	100	9232		
	7.8	425.5	1.8	180	PC080+SB110	10320	
	5.8	513	1.3	240		10320	
	4.7	597	1	300		10320	
	4.7	638.9	2	300		10320	
	3.5	826	1.4	400		10320	
	2.8	984	1.1	500		10320	
	2.3	1181	1	600	SB050/110	10320	
	1.9	1411	0.9	750		10320	
	2.8	995.5	1.6	500		SB063/130	13500
1.9	1471	1.2	750	13500			
1.2	2132	0.8	1200	13500			
0.75	280	22.8	2.7	5			SB050
	186.7	34	2.1	7.5	1805		
	140	44	1.6	10	1987		
	93.3	63	1.2	15	2274		
	70	81	0.9	20	2503		
	93.3	63.7	2.2	15	SB063	2973	
	70	83	1.6	20		3272	
	56	100	1.3	25		3524	
	46.7	114	1.4	30		3745	
	35	143	1	40		4122	
	56	102.3	2	25		4160	
	46.7	117	2	30		4421	
	35	147	1.5	40		4865	
	28	177	1.2	50	5241		
	23.3	200	1	60	5569		
	18.7	280.1	0.9	75	PC080+SB075	6000	
	15.6	313	1	90		6375	
	28	184.2	1.8	50	SB090	5799	
	23.3	212	1.5	60		6163	
	17.5	258	1.1	80		6783	
	14	302	0.9	100		7306	
	15.6	326.9	1.7	90		PC080+SB090	7054
	11.7	405	1.2	120			7764
	9.3	483	0.9	150	8180		
	7.8	543	0.7	180	8180		
	17.5	274.2	1.9	80	SB110		8571
	14	322	1.5	100			9232
	11.7	429.8	2.2	120	PC080+SB110	9811	
	9.3	506	1.7	150		10320	
	7.8	580	1.3	180		10320	
	5.8	700	0.9	240		10320	
	4.7	871.2	1.5	300		SB050/110	10320
3.5	1126	1.1	400	10320			
5.8	712.2	1.4	240	PC080+SB130	13500		
4.7	813	1.1	300		13500		
2.8	1357.5	1.1	500		SB063/130	13500	
						13500	



P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)
0.75	2.3	1631	1	600		13500
	1.9	2005	0.9	750	SB063/130	13500
	1.6	2283	0.8	900		13500
1.1	186.7	49.5	2.6	7.5		2359
	140	65	2	10		2597
	93.3	93	1.5	15	SB063	2973
	70	122	1.1	20		3272
	56	146	0.9	25		3524
	46.7	167	1	30		3745
	93.3	95.7	2.1	15		3509
	70	123	1.7	20		3862
	56	150	1.3	25	SB075	4160
	46.7	171	1.3	30		4421
	35	216	1	40		4865
	35	225.1	1.6	40		5383
	28	270	1.3	50	SB090	5799
	23.3	311	1	60		6163
	28	281.4	2.3	50		7328
	23.3	324	1.9	60		7787
	17.5	402	1.3	80	SB110	8571
	14	473	1	100		9232
	19	398	2.5	73.6		8298
	14.3	515	1.8	98.2		9133
	11.4	609	1.5	122.7	PC090+SB110	9838
	9.5	693	1.1	147.3		10320
	7.1	840	0.8	196.4		10320
	17.5	408.2	2.1	80		11210
	14	480	1.5	100	SB130	12076
	19	404	3.5	73.6		10853
	14.3	515	2.6	98.2		11945
	11.4	619	2	122.7	PC090+SB130	12868
	9.5	693	1.6	147.3		13500
	7.1	855	1.2	196.4		13500
5.7	978	0.9	245.5		13500	
4.7	1312.1	1.3	300		13500	
3.5	1671	1	400	SB063/130	13500	
2.8	1991	0.8	500		13500	
1.5	186.7	67.5	1.9	7.5		2359
	140	89	1.5	10		2597
	93.3	127	1.1	15	SB063	2973
	70	166	0.8	20		3272
	140	90	2.2	10		3065
	93.3	130	1.5	15		3509
	70	168	1.3	20	SB075	3862
	56	205	1	25		4160
	46.7	233	1	30		4421
	70	171.9	2.1	20		4273
	56	210	1.6	25		4603
	46.7	239	1.7	30		4891
	35	307	1.2	40	SB090	5383
	28	368	0.9	50		5799
	23.3	424	0.8	60		6163
	35	319.2	2.2	40		6803
	28	384	1.7	50		7328
	23.3	442	1.4	60	SB110	7787
	17.5	548	0.9	80		8571
	19	543	1.9	73.6		8298
	14.3	703	1.3	98.2	PC090+SB110	9133



P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)	
1.5	11.4	831	1.1	122.7	PC090+SB110	9838	
	9.5	946	0.8	147.3		10320	
	17.5	556.6	1.5	80	SB130	11210	
	14	655	1.1	100		12076	
	19	550	2.6	73.6	PC090+SB130	10853	
	14.3	703	1.9	98.2		11945	
	11.4	845	1.5	122.7		12868	
	9.5	998	1.1	147.3		13500	
	7.1	1165	0.8	196.4		13500	
	4.7	1789.3	1	300		SB063/130	13500
	3.5	2279	0.7	400	13500		
	2.2	186.7	100.2	1.8	7.5	SB075	2785
140		132	1.5	10	3065		
93.3		191	1	15	3509		
186.7		101.3	2.9	7.5	SB090	3081	
140		134	2.3	10		3391	
93.3		194	1.9	15		3882	
70		252	1.4	20		4273	
56		308	1.1	25		4603	
46.7		351	1.2	30		4891	
70		255.1	2.5	20		5399	
56		315	2.2	25		5816	
46.7		356	2	30		6181	
35		468	1.5	40	6803		
28		563	1.2	50	7328		
23.3		648	1	60	7787		
35		468.2	2.2	40	8897		
28		563	1.7	50	9584		
23.3		648	1.4	60	10185		
17.5		816	1	80	11210		
3		186.7	136.6	1.4	7.5	SB075	2785
		140	180	1.1	10		3065
	93.3	261	0.8	15	3509		
	186.7	138.1	2.1	7.5	SB090	3081	
	140	182	1.7	10		3391	
	93.3	264	1.4	15		3882	
	70	344	1	20		4273	
	56	420	0.8	25		4603	
	46.7	479	0.9	30		4891	
	93.3	264	2.5	15		4905	
	70	348	1.9	20		5399	
	56	430	1.6	25		5816	
	46.7	485	1.5	30	6181		
	35	638	1.1	40	6803		
	28	767	0.9	50	7328		
	56	429.8	2.2	25	7607		
	46.7	491	2.1	30	8084		
	35	638	1.6	40	8897		
	28	767	1.3	50	9584		
	23.3	884	1	60	10185		
	17.5	1113	0.8	80	11210		
4	186.7	184.2	1.6	7.5	SB090	3081	
	140	243	1.3	10		3391	
	93.3	352	1	15		3882	
	70	458	0.8	20		4273	
	140	242.8	2.5	10	SB110	4285	
	93.3	352	1.9	15		4905	
	70	464	1.4	20		5399	



P1 (kW)	n2 (1/min)	M2 (Nm)	sf	i	Typ	Fr2 (N)	
4	56	573	1.2	25	SB110	5816	
	46.7	647	1.1	30		6181	
	56	573	1.6	25	SB130	7607	
	46.7	655	1.6	30		8084	
	35	851	1.2	40		8897	
	28	1023	1	50		9584	
	23.3	1179	0.8	60	SB150	10185	
	28.0	1037	1.4	50		13103	
	23.3	1195	1.1	60		13924	
	17.5	1484	0.8	80		15325	
14	1746	0.6	100	16508			
4.8	186.7	221	1.3	7.5	SB090	3081	
	140	291	1.1	10		3391	
	93.3	422	0.9	15		3882	
	186.7	221	2.5	7.5	SB110	3893	
	140	291	2.1	10		4285	
	93.3	422	1.6	15		4905	
	70	557	1.2	20		5399	
	56	688	1	25		5816	
	56	687.6	1.4	25		7607	
	46.7	786	1.3	30		8084	
	35	1022	1	40	8897		
	28	1228	0.8	50	9584		
	5.5	186.7	253.2	2.2	7.5	SB110	3893
		140	334	1.8	10		4285
93.3		484	1.4	15	4905		
70		638	1	20	5399		
140		333.9	2.5	10	SB130	5605	
93.3		490	1.9	15		6416	
70		645	1.4	20		7062	
56		788	1.2	25		7607	
46.7		900	1.2	30		8084	
35		1171	0.9	40		8897	
46.7		934	1.3	30		11051	
35.0		1171	1.3	40	SB150	12163	
28.0		1426	1.0	50	1303		
7.5		186.7	345.3	1.6	7.5	SB110	3893
	140	455	1.3	10	4285		
	93.3	660	1	15	4905		
	186.7	349.2	2.1	7.5	SB130	5092	
	140	455	1.8	10		5605	
	93.3	668	1.4	15		6416	
	70	880	1	20		7062	
	56	1074	0.9	25		7607	
	46.7	1228	0.8	30		8084	
	35	1596	0.7	40		8897	
	70	880	1.5	20	SB150	9654	
	56	1074	1.1	25		10400	
	46.7	1274	0.9	30		11051	
	186.7	423.6	1.3	7.5		SB110	3893
9.2	186.7	428.3	1.8	7.5	SB130	5092	
	140	559	1.5	10		5605	
	93.3	819	1.1	15		6416	
	186.7	512	2.3	7.5	SB150	6962	
11	140	675	1.8	10	SB150	7663	
	93.3	990	1.3	15		8771	
	70	1291	1.0	20		9654	
	140	675	1.8	10		7663	